CLAIMS

1. A wireless ad-hoc communication system constituted by a plurality of terminals, comprising:

a first terminal that encrypts a payload of a broadcast frame and that transmits the broadcast frame; and

a second terminal that receives the broadcast frame and that decodes the payload of the broadcast frame,

wherein the first terminal encrypts the payload of the

10 broadcast frame using a broadcast encryption key of the

first terminal, and

the second terminal decodes the payload of the broadcast frame using the broadcast encryption key of the first terminal.

15

20

25

5

2. The wireless ad-hoc communication system according to claim 1, wherein the second terminal includes:

an encryption-key management list table having at least an encryption-key management list comprising a set of a terminal identifier of the first terminal and the broadcast encryption key of the first terminal;

means for searching the encryption-key management list table based on the terminal identifier of the first terminal included in a start-terminal identifier of the received broadcast frame to extract the corresponding broadcast

encryption key of the first terminal; and

means for decoding the payload of the broadcast frame using the extracted broadcast encryption key of the first terminal.

5

20

25

3. The wireless ad-hoc communication system according to claim 1, wherein the first terminal includes:

a generated-key table that stores the broadcast encryption key of the first terminal;

means for encrypting the payload of the broadcast frame using the broadcast encryption key of the first terminal stored in the generated-key table; and

means for transmitting the encrypted broadcast frame.

15 4. A terminal comprising:

an encryption-key management list table having at least one encryption-key management list comprising a set of a terminal identifier of a different terminal and a broadcast encryption key of the different terminal;

means for searching the encryption-key management list table for the encryption-key management list including a start-terminal identifier of a received broadcast frame to extract the corresponding broadcast encryption key; and

means for decoding a payload of the broadcast frame using the extracted broadcast encryption key.

5. A terminal comprising:

an encryption-key management list table having at least one encryption-key management list that stores a unicast encryption key between said terminal and a different terminal and a broadcast encryption key of the different terminal in association with a terminal identifier of the different terminal;

received frame is a broadcast address, searching the encryption-key management list table for the encryption-key management list including a start-terminal identifier of the frame to extract the corresponding broadcast encryption key as an encryption key, and when the end-terminal identifier of the received frame is other than a broadcast address, searching the encryption-key management list table for the encryption-key management list including a start-terminal identifier of the frame to extract the corresponding unicast encryption key as the encryption key; and

means for decoding a payload of the frame using the extracted encryption key.

6. A terminal comprising:

20

a generated-key table that stores a broadcast 25 encryption key of said terminal;

means for encrypting a payload of a broadcast frame using the broadcast encryption key; and means for transmitting the encrypted broadcast frame.

7. A terminal comprising:

10

15

a generated-key table that stores a broadcast encryption key of said terminal;

an encryption-key management list table having at least one encryption-key management list that stores a unicast encryption key between said terminal and a different terminal in association with a terminal identifier of the different terminal;

means for, when a frame to be transmitted is a broadcast frame, encrypting a payload of the broadcast frame using the broadcast encryption key of the generated-key table, and when the frame to be transmitted is a unicast frame, searching the encryption-key management list table for the encryption-key management list including an endterminal identifier of the unicast frame to encrypt a 20 payload of the unicast frame using the corresponding unicast encryption key; and

means for transmitting the encrypted frame.

8. A terminal comprising:

means for encrypting a terminal identifier and a 25

broadcast encryption key of said terminal using a unicast encryption key of a transmission-destination terminal; and

means for transmitting the encrypted terminal identifier and broadcast encryption key of said terminal to the transmission-destination terminal.

9. A terminal comprising:

5

10

an encryption-key management list table having at least one encryption-key management list that stores a broadcast encryption key of a different terminal in association with a terminal identifier of the different terminal;

means for encrypting the encryption-key management list using a unicast encryption key of a transmission-destination terminal; and

means for transmitting the encrypted encryption-key management list to the transmission-destination terminal.

10. A terminal comprising:

means for receiving a terminal identifier and a

20 broadcast encryption key of a different terminal from the
different terminal;

means for encrypting the terminal identifier and the broadcast encryption key of the different terminal using a broadcast encryption key of said terminal; and

25 means for broadcasting the encrypted terminal

identifier and broadcast encryption key of the different terminal.

- 11. A method for decoding a broadcast frame in a terminal that includes an encryption-key management list table having at least one encryption-key management list comprising a set of a terminal identifier of a different terminal and a broadcast encryption key of the different terminal, the method comprising the steps of:
- searching the encryption-key management list table for the encryption-key management list including a start-terminal identifier of a received broadcast frame to extract the corresponding broadcast encryption key; and

decoding a payload of the broadcast frame using the 15 extracted broadcast encryption key.

12. A method for encrypting a broadcast frame in a terminal that includes a generated-key table storing a broadcast encryption key of said terminal, the method comprising the steps of:

encrypting a payload of the broadcast frame using the broadcast encryption key stored in the generated-key table; and

transmitting the encrypted broadcast frame.

20

13. A method for distributing a broadcast encryption key in a second terminal, comprising the steps of:

receiving a terminal identifier and a broadcast encryption key of a first terminal that are encrypted using a unicast encryption key between the first terminal and the second terminal;

decoding the encrypted terminal identifier and broadcast encryption key of the first terminal using the unicast encryption key;

encrypting a terminal identifier and a broadcast encryption key of the second terminal using the unicast encryption key; and

15

25

transmitting the encrypted terminal identifier and broadcast encryption key of the second terminal to the first terminal.

14. A method for distributing a broadcast encryption key in a second terminal, comprising the steps of:

receiving a terminal identifier and a broadcast

20 encryption key of a first terminal that are encrypted using a unicast encryption key between the first terminal and the second terminal;

decoding the encrypted terminal identifier and broadcast encryption key of the first terminal using the unicast encryption key;

encrypting the terminal identifier and the broadcast encryption key of the first terminal using a broadcast encryption key of the second terminal; and

transmitting the encrypted terminal identifier and broadcast encryption key of the first terminal to a third terminal.

15. A program that causes a terminal including an encryption-key management list table having at least one encryption-key management list comprising a set of a terminal identifier of a different terminal and a broadcast encryption key of the different terminal to execute the steps of:

searching the encryption-key management list table for the encryption-key management list including a start-terminal identifier of a received broadcast frame to extract the corresponding broadcast encryption key; and

decoding a payload of the broadcast frame using the extracted broadcast encryption key.

20

15

10

16. A program that causes a terminal including a generatedkey table that stores a broadcast encryption key of said terminal to execute the steps of:

encrypting a payload of a broadcast frame using the 25 broadcast encryption key stored in the generated-key table;

and

15

25

transmitting the encrypted broadcast frame.

17. A program that causes a second terminal to execute the
5 steps of:

receiving a terminal identifier and a broadcast encryption key of a first terminal that are encrypted using a unicast encryption key between the first terminal and the second terminal;

decoding the encrypted terminal identifier and broadcast encryption key of the first terminal using the unicast encryption key;

encrypting a terminal identifier and a broadcast encryption key of the second terminal using the unicast encryption key; and

transmitting the encrypted terminal identifier and broadcast encryption key of the second terminal to the first terminal.

20 18. A program that causes a second terminal to execute the steps of:

receiving a terminal identifier and a broadcast encryption key of a first terminal that are encrypted using a unicast encryption key between the first terminal and the second terminal;

decoding the encrypted terminal identifier and broadcast encryption key of the first terminal using the unicast encryption key;

encrypting the terminal identifier and the broadcast encryption key of the first terminal using a broadcast encryption key of the second terminal; and

transmitting the encrypted terminal identifier and broadcast encryption key of the first terminal to a third terminal.